Application No.: 10/522,059 MAT-8640US

Amendment Dated: December 15, 2010

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A method of manufacturing a plasma display

panel, the method comprising the steps of:

providing a substrate holder above a source of deposition material, the

substrate holder including:

a plurality of first frames for holding a plurality of substrates for a

respective plurality of plasma display panels, said plurality of first frames have

ahave an inner protrusion between them which extends from below a bottom

surface of the substrate along a side surface of the substrate to a height above

the substrate and greater than a height of the substrate without being

superimposed over the top surface of the substrate, said inner protrusion

extending in a straight direction; and

a plurality of second frames each having a respective opening, curved

outer protrusions situated between each of the second frames and the plurality

of first frames so that the substrates are on one side of each of the curved

outer protrusions and each respective opening is on another side of each of the

<u>curved outer</u> protrusions, the protrusions also extending above the substrates

without being superimposed over the tops of the substrates, and an

unobstructed path exists from said source of deposition material to a top

surface of said substrate;

providing the plasma display panel which is held by the substrate holder for

deposition;

spraying said deposition material onto said bottom surface of said substrate

from below the substrate;

Application No.: 10/522,059 MAT-8640US

Amendment Dated: December 15, 2010

and permitting an additional amount of said deposition material to flow through said opening from below the substrate.

2. (Previously Presented) The method of manufacturing a plasma display panel as defined in Claim 1, wherein heights of the protrusion and the protrusions are between 1 mm and 100 mm.

- 3. (Previously Presented) The method of manufacturing a plasma display panel as defined in Claim 1, the first frame comprising holding means including support means for supporting the plurality of substrates from underneath and positioning means for positioning the plurality of substrates in a planar direction, wherein the plurality of substrates are held by fitting the plurality of substrates to the positioning means and placing the plurality of substrates on the support means.
- 4. (Currently Amended) A substrate holder system for a plasma display panel, the substrate holder system comprising:

a plurality of first frames for holding a plurality of substrates for a respective plurality of plasma display panels, said plurality of first frames being provided with a with an inner protrusion between them which extends from below a bottom surface of the substrate along a side surface of the substrate to a height above the substrate greater than a height of the substrate without being superimposed over the top surface of the substrate, said inner protrusion extending in a straight direction,

a plurality of second frames each having a respective opening, <u>curved outer</u> protrusions situated between each of the second frames and the plurality of first frames so that the substrates are on one side of each of the <u>curved outer</u> protrusions and each respective opening is on another side of each of the <u>curved outer</u> protrusions, the <u>curved outer</u> protrusions also extending above the substrates without being superimposed over the tops of the substrates;

and a source of deposition material below said substrate which sprays said deposition material towards the bottom surface of the substrate and through the opening;

522,059 MAT-8640US

Application No.: 10/522,059 Amendment Dated: December 15, 2010

wherein an unobstructed path exists from said source of deposition material to a top surface of said substrate.

5. (Previously Presented) The substrate holder system for a plasma display panel as defined in Claim 4, wherein heights of the protrusion and the protrusions are between 1 mm and 100 mm.

- 6. (Previously Presented) The substrate holder system for a plasma display panel as defined in Claim 4, the first frame comprising holding means including support means for supporting the plurality of substrates from underneath and positioning means for positioning the plurality of substrates in a planar direction, wherein the plurality of substrates are held by fitting the plurality of substrates to the positioning means and placing the plurality of substrates on the support means.
- 7. (Previously Presented) The substrate holder system for a plasma display panel as defined in Claim 4, wherein the first frame includes a plurality of supports separated from each other which extend below the bottom surface of the plurality of substrates.
- 8. (Previously Presented) The substrate holder system for a plasma display panel as defined in Claim 4, said second frame maintained with said opening while the plurality of substrates are situated in said first frame.
- 9. (Currently Amended) A method of manufacturing a plasma display panel as defined in Claim 1, wherein the <u>curved outer</u> protrusions curve away from the plurality of substrates.